

## Übersicht

# Wandkühlregal VULCANO VC60 SL 187, 1970 breit

Tecnodom

Produktnummer: VC60187SLCGINOX

## Optionen



## Beschreibung

The wall cooling shelf for sausage and dairy products without side glasses for good and sales-promoting presentation of the goods. The goods are very well lit due to the lamps installed on the side. The cooling wall shelf fits perfectly in restaurants, supermarkets and butchers and is ideal for small to large businesses. The electronic thermostat constantly monitors and corrects the temperature of the cooled air flow. In this way, the exhibited products always maintain the ideal temperature. Technology and design of the wall cooling shelf: 100% made in Italy

## Commissioning / cleaning

The installation and installation of the cooling shelf is very easy, since it is operated via a standard 230 V socket. The multi-part floor panels can be lifted up and allow easy access to clean the tub. The removable front cover allows easy cleaning of the condenser and maintenance of the unit. Defrosting is time-controlled and automatic.

## properties

- Large exhibition area on 4 shelves, non-toxic white lacquered, with rails for price tags, without side rails
- Laterally installed lamps for uniform lighting of the goods
- electronic control, digital display
- automatic defrost by compressor stop
- automatic condensation evaporation
- tested ambient temperature + 30 ° C (at 55% humidity) without surcharge

## Produktinformationen

### Technische Daten

|                                  |                                                        |
|----------------------------------|--------------------------------------------------------|
| Auslagefläche m2:                | 2.94                                                   |
| Beleuchtung:                     | Neon                                                   |
| Gerätetyp:                       | VULCANO VC60-SL                                        |
| Nachtrollo:                      | nein                                                   |
| Tiefe der Auslagefläche mm:      | 260                                                    |
| Elektroanschluss:                | 230V / 50 Hz / 1N, steckerfertig mit Schweizer Adapter |
| Kühlung:                         | luftgekühlt, steckerfertig, zentralgekühlt             |
| Temperaturbereich °C:            | +3/+5                                                  |
| Thermostat:                      | digital                                                |
| Abtauung:                        | automatisch mit Tauwasserverdunstung                   |
| Anschlussleistung:               | 2370 W                                                 |
| geprüfte Umgebungstemperatur °C: | + 30 (bei 55% Luftfeuchtigkeit)                        |
| Kälteleistung:                   | 1980 W / VT -10 °C                                     |
| Material aussen:                 | CNS (Inox), Stahlblech pulverlackiert                  |
| Türe:                            | Glas-Drehtüren                                         |
| Breite mm:                       | 1970                                                   |
| Tiefe mm:                        | 650                                                    |
| Höhe mm:                         | 1958                                                   |
| Füsse:                           | höhenverstellbar                                       |
| Gewicht kg:                      | 255                                                    |