

Übersicht

Wandkühlregal VULCANO VC60 SL 140, 1500 breit

Tecnodom

Produktnummer: VC60140SLCGINOX

Optionen



Beschreibung

The wall cooling shelf for sausage and dairy products without side glasses for good and sales-promoting presentation of the goods. The goods are very well lit due to the lamps installed on the side. The cooling wall shelf fits perfectly in restaurants, supermarkets and butchers and is ideal for small to large businesses. The electronic thermostat constantly monitors and corrects the temperature of the cooled air flow. In this way, the exhibited products always maintain the ideal temperature. Technology and design of the wall cooling shelf: 100% made in Italy

Commissioning / cleaning

The installation and installation of the cooling shelf is very easy, since it is operated via a standard 230 V socket. The multi-part floor panels can be lifted up and allow easy access to clean the tub. The removable front cover allows easy cleaning of the condenser and maintenance of the unit. Defrosting is time-controlled and automatic.

properties

- Large exhibition area on 4 shelves, non-toxic white lacquered, with rails for price tags, without side rails
- Laterally installed lamps for uniform lighting of the goods
- electronic control, digital display
- automatic defrost by compressor stop
- automatic condensation evaporation
- tested ambient temperature + 30 ° C (at 55% humidity) without surcharge

Produktinformationen

Technische Daten

Auslagefläche m2:	2.19
Beleuchtung:	Neon
Gerätetyp:	VULCANO VC60-SL
Nachtrollo:	nein
Tiefe der Auslagefläche mm:	260
Elektroanschluss:	230V / 50 Hz / 1N, steckerfertig mit Schweizer Adapter
Kühlung:	luftgekühlt, steckerfertig, zentralgekühlt
Temperaturbereich °C:	+3/+5
Thermostat:	digital
Abtauung:	automatisch mit Tauwasserverdunstung
Anschlussleistung:	1496 W
geprüfte Umgebungstemperatur °C:	+ 30 (bei 55% Luftfeuchtigkeit)
Kälteleistung:	1540 W / VT -10 °C
Material aussen:	CNS (Inox), Stahlblech pulverlackiert
Türe:	Glas-Drehtüren
Breite mm:	1500
Tiefe mm:	650
Höhe mm:	1958
Füsse:	höhenverstellbar
Gewicht kg:	200